

**Amendments to the Claims:**

Claims 1-28 (Cancelled)

29. **(Currently amended)** A trackball device comprising:

a sphere including magnetic material;

a support ~~configured to rotatably support~~ supporting said sphere, said support including first, second and third supporting members arranged in contact with said sphere at respectively spaced apart locations;

a rotation detector configured to detect rotation of said sphere and output a signal indicating rotation of said sphere;

a controller operably coupled to said rotation detector and being configured to generate a specific output signal responsive to the signal from said rotation detector indicating rotation of said sphere; and

an informer including an electromagnet;

wherein said sphere is disposed in a magnetic flux circuit generated by said electromagnet; such that magnetic flux of said magnetic flux circuit goes from said electromagnet through said first supporting member, said sphere, and said second supporting member, and returns to said electromagnet, with said sphere being located in said magnetic flux circuit between said first and second supporting members; and

wherein said informer is operable to change a friction force of said sphere with respect to said support by causing said electromagnet to generate a magnetic attractive force to ~~influence~~ attract said sphere to said first and second supporting members based on said specific output signal from said controller.

30. **(Currently amended)** The trackball device of claim 29, wherein said electromagnet has a core with first and second ends; and

wherein said ~~support includes at least a~~ first supporting member is coupled to said first end of said core, ~~a~~ said second supporting member is coupled to said second end of said core, and ~~a~~ said third supporting member is independent of said core.

31. **(Previously presented)** The trackball device of claim 30, wherein a surface material of said first supporting member, said second supporting member, and said third supporting member is the same as a surface material of said sphere.

32. **(Previously presented)** The trackball device of claim 30, further comprising a first switch arranged to be depressed by said sphere via said third supporting member; wherein said controller is operable to detect a state of said first switch.

33. **(Previously presented)** The trackball device of claim 30, wherein said controller is operable to switch alternately a direction of the magnetic flux generated by the electromagnet.

34. **(Previously presented)** The trackball device of claim 29, wherein said controller is operable to switch alternately a direction of the magnetic flux generated by the electromagnet.

35. **(Previously presented)** The trackball device of claim 29, further comprising a permanent magnet configured to have a magnetic field that influences said sphere so as to force said support against said sphere.

36. **(Previously presented)** The trackball device of claim 35, wherein said permanent magnet is located so that a direction of magnetic lines generated by said permanent magnet coincides with a direction of magnetic lines generated by said electromagnet.

37. **(Currently amended)** The trackball device of claim 35, wherein  
said electromagnet has a core with first and second ends, said ~~support includes at least a~~  
first supporting member is coupled to said first end of said core, ~~a said~~ second supporting  
member is coupled to said second end of said core, and ~~a said~~ third supporting member is  
independent of said core.

38. **(Previously presented)** The trackball device of claim 37, wherein  
a surface material of said first supporting member, said second supporting member, and  
said third supporting member is the same as a surface material of said sphere.

39. **(Previously presented)** The trackball device of claim 37, further comprising  
a first switch arranged to be depressed by said sphere via said third supporting member;  
wherein said controller is operable to detect a state of said first switch.

40. **(Previously presented)** The trackball device of claim 35, wherein  
said controller is operable to switch alternately a direction of the magnetic flux generated  
by said electromagnet.

41. **(Currently amended)** An input device comprising  
a trackball device, and  
at least one switch disposed around said trackball device,  
wherein said trackball device comprises:  
a sphere including a magnetic material;  
a support ~~configured to rotatably support~~ supporting said sphere, said support  
including first, second and third supporting members arranged in contact with said sphere at  
respectively spaced apart locations;

a rotation detector configured to detect rotation of said sphere and output a signal indicating rotation of said sphere;

a controller operably coupled to said rotation detector and being configured to generate a specific output signal responsive to the signal from said rotation detector indicating rotation of said sphere; and

an informer including an electromagnet;

wherein said sphere is disposed in a magnetic flux circuit generated by said electromagnet; such that magnetic flux of said magnetic flux circuit goes from said electromagnet through said first supporting member, said sphere, and said second supporting member, and returns to said electromagnet, with said sphere being located in said magnetic flux circuit between said first and second supporting members; and

wherein said informer is operable to change a friction force of said sphere with respect to said support by causing said electromagnet to generate a magnetic attractive force to ~~influence~~ attract said sphere to said first and second supporting members based on said specific output signal from said controller.

42. **(Currently amended)** The input device of claim 41, wherein

said electromagnet has a core with first and second ends; and

wherein said ~~support includes at least a~~ first supporting member is coupled to said first end of said core, ~~a~~ said second supporting member is coupled to said second end of said core, and ~~a~~ said third supporting member is independent of said core.

43. **(Previously presented)** The input device of claim 41, further comprising

a permanent magnet configured to have a magnetic field that influences said sphere so as to force said support against said sphere.

44. **(Currently amended)** A vehicle comprising

a vehicle body having a vehicle cabin therein,  
a drive wheel supporting said vehicle body, and  
a trackball device provided in said vehicle cabin,  
wherein said trackball device comprises:

a sphere including magnetic material;

a support ~~configured to rotatably support~~ supporting said sphere, said support including first, second and third supporting members arranged in contact with said sphere at respectively spaced apart locations;

a rotation detector configured to detect rotation of said sphere and output a signal indicating rotation of said sphere;

a first controller operably coupled to said rotation detector and being configured to generate a specific output signal responsive to the signal from said rotation detector indicating rotation of said sphere; and

an informer including an electromagnet;

wherein said sphere is disposed in a magnetic flux circuit generated by said electromagnet; such that magnetic flux of said magnetic flux circuit goes from said electromagnet through said first supporting member, said sphere, and said second supporting member, and returns to said electromagnet, with said sphere being located in said magnetic flux circuit between said first and second supporting members; and

wherein said informer is operable to change a friction force of said sphere with respect to said support by causing said electromagnet to generate a magnetic attractive force to ~~influence~~ attract said sphere to said first and second supporting members based on said specific output signal from said controller.

45. **(Currently amended)** The vehicle of claim 44, wherein  
said electromagnet has a core with first and second ends; and

wherein said ~~support includes at least a~~ first supporting member is coupled to said first end of said core, ~~a~~ said second supporting member is coupled to said second end of said core, and ~~a~~ said third supporting member is independent of said core.

46. **(Previously presented)** The vehicle of claim 44, further comprising:  
a second controller configured to receive the output signal from said first controller; and  
electronic equipment configured to be controlled by said second controller.

47. **(Previously presented)** The vehicle of claim 44, wherein  
said electronic equipment includes a display for displaying at least one of a pointer and a  
cursor, and rotation of said sphere causes movement of at least one of said pointer and said  
cursor on said display.

48. **(Previously presented)** The vehicle of claim 44, wherein  
said trackball device is disposed in a central position of a full width of said vehicle cabin.

49. **(Previously presented)** The vehicle of claim 44, further comprising  
two seats in a front portion of said vehicle cabin, wherein said trackball device is  
disposed between said two seats.

50. **(Previously presented)** A vehicle of claim 44, further comprising  
a permanent magnet configured to have a magnetic field that influences said sphere so as  
to force said support against said sphere.

51. **(Previously presented)** The vehicle of claim 50, further comprising:  
a second controller for receiving the output signal from said first controller; and  
electronic equipment controlled by said second controller.

52. **(Previously presented)** The vehicle of claim 50, wherein said electronic equipment includes a display for displaying at least one of a pointer and a cursor, and rotation of said sphere causes movement of at least one of said pointer and said cursor on said display.

53. **(Previously presented)** The vehicle of claim 50, wherein said trackball device is disposed in a central position of a full width of said vehicle cabin.

54. **(Previously presented)** The vehicle of claim 50, further comprising two seats in a front portion of said vehicle cabin, wherein said trackball device is disposed between said two seats.

55. **(Previously presented)** A trackball device comprising:  
a sphere consisting of one of martensite stainless steel and ferrite stainless steel;  
a support configured to rotatably support said sphere;  
a rotation detector configured to detect rotation of said sphere;  
a controller configured to generate a specific output signal responsive to a signal from said rotation detector; and

an informer including an electromagnet, and being configured to generate auxiliary information responsive to rotating of said sphere, the auxiliary information being based on the output signal from said controller;

wherein said sphere is disposed in a magnetic flux circuit generated by said electromagnet, and said informer is operable to generate the auxiliary information by causing said electromagnet to generate a magnetic attractive force to influence said sphere.

56. **(New)** The trackball device of claim 29, wherein

said first, second and third supporting members support said sphere at three locations disposed equiangularly.

57. **(New)** The input device of claim 41, wherein  
said first, second and third supporting members support said sphere at three locations disposed equiangularly.

58. **(New)** The vehicle of claim 44, wherein  
said first, second and third supporting members support said sphere at three locations disposed equiangularly.